

Winona Concrete & Pipe Products Ltd.

489 Main Street West, Grimsby, Ontario L3M 1T4
Ph. 905-945-8515 Email: info@winonaconcrete.com Fax. 905-945-1149
Southern Ontario Toll Free 800-361-8515

Concrete Septic Tank (Trickle)




Certified
Std.B66-05

Date : Feb. 1, 2009

Model : 127T-PL20

Capacity: 12,700 litres (2800 gal)



Drawings are dimensional (not necessarily to scale)
with unit of measure in millimeters unless noted otherwise.



Product Information ...

- 1) **POLYLOK ACCESS RISERS** (20" or 24" dia.) cast-in place. Additional 6" high gasketed sections may be added to suit.
- 2) **POLYLOK RISER LID** fastened to riser section with (6) stainless hex head self tappers (supplied)
- 3) **"DANGER" WARNING LABEL** (English / French) shown on lid surface.
- 4) **INLET / OUTLET BAFFLES** are 100 mm PVC-BDS Fittings / Pipe, fabricated & supplied with tank for contractor to affix on to end of soil pipe entering tank through 100 mm flexible rubber boot.

NEW - Effective Jan.2007: An Effluent Filter must be installed at outlet. Various styles available upon request.




- 5) Cement is Portland Type 10 &/or 30 unless noted otherwise.

Minimum 28-day Concrete Strength: 32 MPa
"NON-SUL". Not suitable for sulphate soils

- 6) Steel Reinforcing as follows:
Top & Bottom 10 mm
Sides 10 mm
Partition 4x4 6/6 WW mesh

- 7) 1/2" Galvanized Wire Rope Lifting Hooks (4) embedded vertically 24" down into side walls.

- 8) Detail view below showing typical Top - Side interface and use of flexible Pipe Boot at inlet & outlet positions.



- 9) Design Burial Depth (cover)1000 mm
Not intended for use in areas of vehicular traffic loading.
"AGINP" Above ground installation not permitted

DRY WEIGHT 25,700 POUNDS

FEB09_S127T_PL20